



TECHNICAL SPECIFICATIONS

AirLink® RV55

Performance Series Routers




| | North America | EMEA | North America | Global | Global |
|---|---|---|--|--|---|
| | LTE | | LTE-A Pro | | LTE-M/ NB-IoT |
| LTE CATEGORY | Cat 4 (WP7610 WP7607) | | Cat 12 (EM7511 EM7565) | | Cat M1/NB1 (WP7702) |
| Peak D/L | Up to 150 Mbps | | Up to 600 Mbps | | Cat-M1: 300kbps Cat-NB1: 27kbps |
| Peak U/L | Up to 50 Mbps | | Up to 150 Mbps | | Cat-M1: 375kbps Cat-NB1: 65kbps |
| 4G LTE Frequency Bands | 1900(B2), AWS(B4), 850(B5), 700(B12), 700(B13), 700(B17), 1700(B66) | 2100(B1), 1800(B3), 2600(B7), 900(B8), 800(B20), 700(B28) | 2100(B1), 1900(B2), 1800(B3), AWS(B4), 850(B5), 2600(B7), 900(B8), 1800(B9), 700(B12), 700(B13), 700(B14), 850(B18), 850(B19), 800(B20), 850(B26), 700(B29), 2300(B30), 1500(B32), TDD B41, TDD B42, TDD B43, TDD B46, CBR5 B48, 1700(B66) | 2100(B1), 1900(B2), 1800(B3), AWS(B4), 850(B5), 2600(B7), 900(B8), 1800(B9), 700(B12), 700(B13), 850(B18), 850(B19), 800(B20), 850(B26), 700(B28), 700(B29), 2300(B30), 1500(B32), TDD B41, TDD B42, TDD B43, TDD B46, CBR5 B48, 1700(B66) | 2100(B1), 1900(B2), 1800(B3), AWS(B4), 850(B5), 900(B8), 700(B12), 700(B13), 700(B17), 850(B18), 850(B19), 800(B20), 850(B26), 700(B28) |
| 3G HSPA/HSPA+ Frequency Bands* | 1900(B2), AWS(B4), 850(B5) | 2100(B1), 900(B8) | 2100(B1), 1900(B2), AWS(B4), 850(B5), 800(B6), 900(B8), 1700(B9), 850(B19) | 2100(B1), 1900(B2), AWS(B4), 850(B5), 800(B6), 900(B8), 1700(B9), 850(B19) | |
| 2G EDGE/GSM/GPRS Frequency Bands | | 900, 1800 | | | 850, 900, 1800, 1900 |
| APPROVALS Regulatory | FCC, IC, PTCRB | GCF, CE | FCC, IC, PTCRB | FCC, IC, PTCRB, GCF, CE, RCM, IFT, Anatel | FCC, IC, PTCRB, GCF, CE, RCM |
| Carrier | Verizon, AT&T, T-Mobile | | Verizon, AT&T/FirstNet, US Cellular, T-Mobile, Telus | Verizon, AT&T, Telstra(Planned) | Verizon(Cat-M), AT&T(Cat-M) |
| PART NUMBER Regulatory | 1104335 | 1104337 | 1104303, 1104302 (Wi-Fi) 1104302 (Wi-Fi) | 1104332, 1104331 (Wi-Fi) 1104331 (Wi-Fi) | 1104333 |

*For carrier-specific band support please refer to the hardware user guide.

| | Specification | Specification |
|-------------------------|--|--|
| HOST INTERFACES | 10/100/1000 Ethernet (RJ45) RS-232 serial port (DB-9) USB 2.0 Micro-B Connector 3 SMA antenna (cellular, diversity, GNSS) 2 RP-SMA antenna (1x1 Wi-Fi, Optional) LTE-M/NB-IoT: 1 SMA (cellular) only, no GNSS or Wi-Fi Active GPS antenna support | SATELLITE NAVIGATION (GNSS) LTE-A Pro Variant: 30 Channel GPS and GLONASS Receiver (Tracking Sensitivity: -160dBm) LTE Variant: 48 Channel Dedicated GNSS Receiver (Tracking Sensitivity: -162 dBm) Accuracy: <2 m (50%), <5 m (90%), <0.2 m/s Acquisition Time: 1s Hot Start Reports: NMEA 0183 V3.0, TAIP, RAP, XORA Multiple Redundant Servers Reliable Store and Forward |
| WI-FI (Optional) | Dual Band 2.4/5GHz Wi-Fi Dual Radio, 802.11 b/g/n/ac (Wave2 Client Mode) Support for 10 clients, WPA2 Enterprise per radio Output power 16dBm Configurable as Dual Band Access Point (AP) or AP+Client Mode Single SSID Support per radio Captive Portal | SECURITY Remote Authentication (LDAP, RADIUS, TACACS+, DMZ) Inbound and Outbound Port filtering Inbound and Outbound Trusted IP MAC Address Filtering PCI compatible Secure Firmware Update |

TECHNICAL SPECIFICATIONS

| | Specification |
|------------------------------|---|
| INPUT/OUTPUT | Configurable I/O pin on power connector <ul style="list-style-type: none"> Digital Input ON Voltage: 2.7 to 36 VDC Configurable Pull-up for dry contact input Digital Open Collector Output > sinking 500 mA Analog Input: 0.5-36 VDC |
| LAN (ETHERNET/USB) | DHCP Server Host Interface Watchdog IP Passthrough PPPoE VLAN |
| SERIAL | TCP/UDP PAD Mode Modbus (ASCII, RTU, Variable) PPP DNP3 Interoperability Dual Serial option (with an accessory) |
| NETWORK AND ROUTING | Network Address Translation (NAT) Reliable Static Route Port Forwarding Dynamic DNS Policy Routing Verizon PNTM NEMO/DMNR IPV6 Gateway VRRP |
| VPN** | IPsec, GRE, and OpenVPN Client Up to 5 concurrent tunnels Split Tunnel Dead Peer Detection (DPD) FIPS 140-2 compatible |
| APPLICATION FRAMEWORK | ALEOS Application Framework (AAF) Lua Scripting Language |
| POWER | Input Voltage: 7 to 36 VDC LTE Idle Power: 900mW (75 mA @ 12VDC) Standby Mode Power: 53 mW (4.4 mA @ 12 VDC) triggered on low voltage, I/O or periodic timer Low voltage disconnect to prevent battery drain Built-in protection against voltage transients including 5 VDC engine cranking and +200 VDC load dump Ignition Sense with time delay shutdown Configurable features and ports to optimize power consumption |
| DIMENSIONS | 119 mm x 33 mm x 85 mm (102 mm including wi-fi connectors) 4.69 in x 1.34 in x 3.35 in (3.70 in including connectors) Weight: 320 g |



| | Specification |
|--------------------------------|---|
| NETWORK MANAGEMENT | Secure mobile network & asset management application available in the cloud or licensed platform in the enterprise data center Fleet wide firmware upgrade delivery Router configuration and template management Router staging over the air and local Ethernet connection Over-the-air software and radio module firmware updates Device Configuration Templates Configurable monitoring and alerting Remote provisioning and airtime activation (where applicable) |
| ROUTER MANAGEMENT | ALMS Local web user interface AT Command Line Interface (Telnet/SSH/Serial) SMS Commands SNMP |
| EVENTS ENGINE | Custom event triggers and reports Configurable interface, no programming Event Types: Digital Input, Network Parameters, Data Usage, Timer, Power, Device Temperature and Voltage Report Types: RAP, SMS, Email, SNMP Trap, TCP (Binary, XML, CSV) Event Actions: Drive Relay Output |
| ENVIRONMENTAL | Operating Temperature: -40°C to +70°C / -40°F to +158°F Operating Temperature (Wi-Fi variant): -30°C to +70°C / -22°F to +158°F Storage Temperature: -40°C to +85°C / -40°F to +185°F Humidity: 95% RH @ 60°C Military Spec MIL-STD-810G conformance to shock, vibration, thermal shock, and humidity IP64 rated ingress protection |
| INDUSTRY CERTIFICATIONS | Safety: IECCE Certification Bodies Scheme (CB Scheme), UL 60950*** Vehicle Usage: E-Mark (UN ECE Regulation 10.04), Rail Usage: EN50155 ISO7637-2, SAE J1455 (Shock & Vibration) Hazardous Environments: Class 1 Div 2– Ambient temperatures of -30°C to +60°C Environmental: RoHS, REACH, WEEE |
| SUPPORT AND WARRANTY | Includes 1st Year AirLink Complete: <ul style="list-style-type: none"> AirLink Management Service (ALMS) Direct 24/7 Technical Support 3-year standard warranty; optional 2-year warranty extension 1-day Accelerated Hardware Replacement available through participating resellers |
| ACCESSORIES | In the Box: DC Power Cable, and Quick Start Guide Other Accessories (sold separately): 2000579 AC Adapter, 12VDC 6000659 DIN Rail Bracket For Antenna options visit: sierrawireless.com/antennas |

** IPsec, GRE and OpenVPN Client are not available in the member states of the EAEU.
*** Ambient temperatures of -30C to +60C

Related AirLink Products

AIRLINK DEVICE MANAGEMENT SOLUTIONS

AirLink Management Service (ALMS)



- Secure, Cloud-based network and asset management
- Remotely deploy, configure, monitor and manage AirLink devices
- Carrier-grade, high availability, secure, global infrastructure

AIRLINK VPN APPLIANCE

AirLink Connection Manager



- VPN appliance built from the ground up for AirLink routers & gateways
- Simplify deployment and management of your VPN solution, extending the enterprise to the network edge for fixed and mobile endpoints
- Carrier agnostic – ACM doesn't require fixed and/or public IP
- Compatible with FIPS 140-2, and always-on VPN capability

AIRLINK ANTENNA SOLUTIONS

AirLink Antennas



- Tested and certified to provide guaranteed performance with all AirLink routers and gateways
- Accelerate deployment with always-on, end-to-end connectivity

About Sierra Wireless

Sierra Wireless (NASDAQ: SWIR) (TSX: SW) is the leading IoT solutions provider that combines devices, network and software to unlock value in the connected economy. Companies globally are adopting IoT to improve operational efficiency, create better customer experiences, improve their business models and create new revenue streams. Whether it's a solution to help a business securely connect edge devices to the cloud, or a software/API solution to help manage processes associated with billions of connected assets, or a platform to extract real-time data to make the best business decisions, Sierra Wireless will work with you to create the right industry-specific solution for your next IoT endeavor. Sierra Wireless has more than 1,300 employees globally and operates R&D centers in North America, Europe and Asia.

For more information, visit www.sierrawireless.com.